

(1) **Type Examination Certificate**

(2) No. of the Type Examination Certificate: **ZP/B157/21** replaces ZP/B129/16

(3) Product: **Anchor device type A**
Type: LUX-top® ONE

(4) Manufacturer: **ST-Quadrat s.a.**
11, rue Flaxweiler
6776 Grevenmacher/ Potaschberg
LUXEMBURG

(5) Site of manufacture: **ST QUADRAT Fall Protection S.A.**
45, rue Fuert
5410 BEYREN
LUXEMBURG

(6) The design of this product and any acceptable variation thereto are specified in the schedule to this Type Examination Certificate.

(7) The certification body of DEKRA Testing and Certification GmbH certifies that this product complies with the fundamental requirements of the standard listed under item 8 below. The examination and test results are set out in the report PB 21-171.

(8) The requirements of the standard are assured by compliance with

DIN EN 795:2012

DIN CEN/TS 16415:2017


(9) This Type Examination Certificate relates only to the design, examination and tests of the specified product in accordance to the standard list. Further requirements of the Directive apply to the manufacturing process and supply of this personal protective equipment. These are not covered by this certificate.

(10) This Type Test Certificate is valid until 2026-10-06.

DEKRA Testing and Certification GmbH
Bochum, 2021-10-07

signed: Kilisch
Managing director

We confirm the correctness of the translation from the German original.
In the case of arbitration only the German wording shall be valid and binding.


Managing director

TRANSLATION

- (11) Appendix to
- (12) **Type Examination Certificate**
ZP/B157/21
- (13) 13.1 Subject and Type
Anchor device type A
Type: LUX-top® ONE

13.2 Description

The anchor device of type LUX-top® ONE (Fig. 1-2) is used to protect a maximum number of two persons against falls from a height. The device is assembled onto surfaces of sufficient strength. The base plate is a metal sheet (t = 4 mm) with a slit that runs centrally along its length.

The lugs (75 x 35 mm) which are created this way are edged opposite at an angle of 90°. In the bridge between the lugs, an oval (42 x 30 mm) is inserted which is used to connect the user's personal protective equipment. The device is fastened to the structure by means of two drill holes (Ø 14 mm) installed at the lugs and by means of appropriate fastening elements. The anchor device can be loaded in any direction and is made of corrosion-resistant steel.





Fig. 1-2: Anchor device of type LUX-top® ONE

- (14) Report
PB 21-171, 2021-10-07