



Stückliste						
Pos.	Menge	Einheit	Benennung	Artikelnr.	Tech. Lieferbed.	Werkstoff
1	1	Stk.	LUX-top® ASP EV 30/2 Ø26 150x150x6 4-Loch	12500		1.4301
2	1	Stk.	LUX-top® Anschlagöse M16 beschriftet	42290		A2
3	1	Stk.	Mutter ISO 4032 (DIN 934) M16	41730		A2-70
4	1	Stk.	Sicherungsscheibe Form S S16	42120		A2
5	4	Stk.	Sechskantschraube ISO 4017 (DIN 933) M10x40	84038		A2-70
6	4	Stk.	Mutter ISO 4032 (DIN 934) M10	84095		A2-70
7	8	Stk.	U-Scheibe ISO 7089 - 10 (DIN 125)	41990		A2
 ST QUADRAT Fall Protection S.A. <a href="http://www.lux-top-absturzicherungen.de">www.lux-top-absturzicherungen.de</a>				Allgemein-Toleranzen ISO 2768-m	Toleranz nach DIN EN 1090-2	Maßstab: 1 : 3 Blattformat: DIN A3
				Bearb. 17.12.2019	Name CR	LUX-top® ASP EV30/2 Ø26 Stahl 150x150x6, 4-Loch
				Gepr.		
				Übersichtszeichnung		Artikelnummer: 12510
REV.	Änderung	Datum	Name	Ursprung		REV. 0 Blatt 1 1 Blätter